

Electric Gas Lift Valve Flow Loop Testing

 Michael Romer, Keegan Johnson, and Tom Murray ExxonMobil Upstream Integrated Solutions
 Levi Honeker, Mahlon Lisk, and Mike Sollid Precise Downhole Services

ALRDC Gas Lift Workshop June 7th-11th 2021





Outline

- EGLV Introduction
- Testing
 - Goals
 - Facility
 - Loop and Skid
- Results
 - Characterization
 - Bonus Tests
 - Erosion
- Summary



EGLV Introduction

EGLV = Electric Gas Lift Valve

- Originally designed for injection applications (EOR)
- Electrically-controlled GLV (0-100% open)
 - One 1/4 in. Tubing Encapsulated Cable (TEC) with 4 conductors
 - ▶ GLVs are daisy-chained with TEC, independently addressed
- A control valve for gas flow rather than a pressure regulator

Specifications

- 1 in. OD conventional GLV form-factor
 - > 3/8 in. (24/64 in.) port and hybrid polymer/metal dart
- 3.5 ft mandrel for 2-7/8 in. tubing standard (for 5.5 in. casing)
- Tubing/casing temperature/pressure sensors at each GLV
 - Electronics tested to 300°F
- Surface controller powered with <30W</p>

	Artificial Lift R&D Council
	P/T Sensors Electrical
	TEC Line
0	Tubing Port
	— Casing Port

Why Use an EGLV?

Advantages

- Know where you're lifting all the time (eliminate multipointing)
- Full injection pressure available (no Δp per valve, fewer valves needed)
- P/T at each valve (live flowing pressure traverses, save a BHP gauge)
- Fully-adjustable injection rate
- Reduced dependence on surface injection control (rough vs. fine-tuning)
- No prod. pressure effect or temp. sensitivity (less slugging, no chattering)
- Check valve and packer optional (annular and tubing lift?)
- Fully-autonomous, closed-loop GL possible (GAPL/PAGL, too)

Disadvantages

- Higher initial cost
- Reliability of downhole electronics
- Conventional GLVs, so tubing workover to change them



Testing Goals

Goals

- Characterize flow performance
- Evaluate power draw vs. applied Δp
- Simulate well unloading with residual solids
- Identify the operational envelope (destructive testing!)



Testing Facility





UIS Friendswood Test Facility

6/11/2021



Test Skid



BACK



Valve Characterization





Normal (Dashed) and Reverse (Solid) Flow

Goal: Characterize valve flow with water

- City water (with some tank rust), downstream pressure atmospheric
- Not much change in the injection performance from 100 to 40% open
- Tested with high (2000 psi) and low pressure (400 psi) pumps to cover full range
- Flow coefficients indicate dart has more impact on tubing-to-casing (reverse) direction
- Can use this data to calculate expected gas throughput under certain conditions

Valve Characterization



- 1200 psi Upstream, 200°F
- EGLV Calculated Injection Normal

- Left: 1 in. Orifice GLV VPC data showing 8, 10, 12, 16, 20, and 24/64 in. ports
- **Right:** A single EGLV from 15 to 100% open
- Stable range of about 300 to 2100 Mscfd for both
- Full characterization would require gas injection at choked flow conditions

6/11/2021

10

Artificial Lift

R&D Council

Leaky Valve





30% **Leakage (% of Total Flow)** 12% 10% 2% 0% 200 600 1000 400 800 n Differential Pressure (psi)

Leakage Past Closed EGLV without Polymer Seal

- Confirmed that **90 gpm** through a **20% open** EGLV is a bad idea (oops)
- High velocity flow removed the polymer from the dart tip
- **Goal:** Determine how much a leaky valve leaks
- Fluid: City water
- **Result:** 10-20% of total flow leaked through depending on the differential pressure

Current Draw



R&D Council

Artificial Lift

- Opening against 1500 psi ∆p is also a bad idea
- Failed leak test,"rolled" polymer
- Reported valve "squealing" during movement and required communications reset—but the motor retained functionality!

- **Goal:** Determine EGLV current draw at various Δp
- Fluid: City water
- **Result:** Current draw increases roughly linearly with Δp
 - More current required to close against flow than open against static pressure

Erosion Testing







Flow Return



- Transitioned to lower capacity pump for erosion testing
- **Goal:** 400 bbl at constant rate, unloading process simulation
 - > 3x the expected annular volume for 2-7/8 in. tubing in 5.5 in. casing, 10kft well
- Valve Position: 100% open
- Fluid: 1% by volume 70/100 mesh sand in city water (residual frac sand)
- Injection Rate: Up to 1 bbl/min (API recommended max. for standard GLV)

6/11/2021





SSO - Passed at 20 gpm



SSO - Failed at 25 gpm

- Seal tests performed at 100 bbl injection intervals
- Dart SSO and standard seat passed 400 bbl test in both flow directions
 - Tested at 20 gpm, 65-80 psi Δp
- Same design failed 200 bbl seal test when injecting at 25 gpm, 120 psi Δp
 - Noted erosion at seat









SSD1 - Passed, Minimal Wear



SSD2 - Passed

BD2 - Passed

- All new designs tested held a liquid seal (200+ psi) after 400 bbl at 25 gpm, casing-to-tubing
- Taller darts (backshell plus seal) reduced effective flow area, resulting in higher Δp and wear
- Minimal erosion noted in boronized seats





Before





Δp Drop Over Time from Outlet Erosion

- Improved seat and dart designs moved wear to the standard valve bodies
- Boronized valve bodies to be tested in Round 3

Summary

EGLV Testing

- Built a custom flow loop to determine EGLV operational envelope
- Characterization showed the EGLV can simulate a wide range of GLV ports
- Conducted unique leak and power draw tests
- ► Original design withstood 20 gpm, 80 psi Δp erosion testing
- Design improvement in progress, boronizing shows promise

Next Steps

- Test with boronized valve bodies
- Optimize dart designs for erosion resistance
- Increase injection rate to define new erosion limit



Acknowledgements, Thank You, & Questions









6/11/2021

Copyright

Rights to this presentation are owned by the company(ies) and/or author(s) listed on the title page. By submitting this presentation to the Gas-Lift Workshop, they grant to the Workshop, the Artificial Lift Research and Development Council (ALRDC) rights to:

- Display the presentation at the Workshop.
- Place it on the <u>www.alrdc.com</u> web site, with access to the site to be as directed by the Workshop Steering Committee.
- Links to presentations on ALRDC's social media accounts.
- Place it on an USB/CD for distribution and/or sale as directed by the Workshop Steering Committee.

Other uses of this presentation are prohibited without the expressed written permission of the company(ies) and/or author(s) who own it and the Workshop Steering Committee.

Artificial Lift

R&D Counci

Disclaimer

The following disclaimer shall be included as the last page of a Technical Presentation or Continuing Education Course. A similar disclaimer is included on the front page of the Gas-Lift Workshop Web Site.

The Artificial Lift Research and Development Council and its officers and trustees, and the Gas-Lift Workshop Steering Committee members, and their supporting organizations and companies (here-in-after referred to as the Sponsoring Organizations), and the author(s) of this Technical Presentation or Continuing Education Training Course and their company(ies), provide this presentation and/or training material at the Gas-Lift Workshop "as is" without any warranty of any kind, express or implied, as to the accuracy of the information or the products or services referred to by any presenter (in so far as such warranties may be excluded under any relevant law) and these members and their companies will not be liable for unlawful actions and any losses or damage that may result from use of any presentation as a consequence of any inaccuracies in, or any omission from, the information which therein may be contained.

The views, opinions, and conclusions expressed in these presentations and/or training materials are those of the author and not necessarily those of the Sponsoring Organizations. The author is solely responsible for the content of the materials.

The Sponsoring Organizations cannot and do not warrant the accuracy of these documents beyond the source documents, although we do make every attempt to work from authoritative sources. The Sponsoring Organizations provide these presentations and/or training materials as a service. The Sponsoring Organizations make no representations or warranties, express or implied, with respect to the presentations and/or training materials, or any part thereof, including any warrantees of title, non-infringement of copyright or patent rights of others, merchantability, or fitness or suitability for any purpose.

