


Using What You've Learned to Improve Your Wells

Design Considerations





Selection of Flow Correlation

Frequently used Vertical Flow Correlations:

- ► Hagedorn and Brown (slug flow regime)
- ▶ Duns and Ros (churn/annular/semi-annular flow regimes)
- Gray (mist flow regime / wet gas wells)

Proprietary methods in WinGLUE:

- ► Mobil Moreland Shell Method (MMSM)
- George Zabaras Method (GZM)

Proprietary methods in Prosper:

- ► Petroleum Experts 2
- ► Petroleum Experts 3
- ▶ Petroleum Experts 5

Other mechanistic models that can provide reliable results:

- Ansari
- Chokshi



Fluid Properties



- Default static fluid gradient for unloading: 0.465 psi/ft
- Where possible, tune black-oil PVT correlations using representative laboratory data.
- Pay particular attention to the following:
 - Production rates (Qoil, Qwater, Qgas, Qgi)
 - ► GOR
 - Water Cut
 - API Gravity
 - Water Gravity
 - ► Gas Gravity (for both produced gas and injection gas)




Kick-off Pressure (Pio of top valve) should be at least 50 psi less than the maximum available injection pressure that can be delivered to the wellhead on a consistent basis (365 days per year).

Rationale:

- 1. Under worst case conditions, there would be zero dP at the depth of the unloading valve if designing for Pio = max available.
- 2. Under certain cases (i.e. high ambient temperatures), compressor may not be able to deliver max available injection pressure.
- 3. When considering valve performance, there is often zero stem travel (or gas passage) at P_{iod}.


Artificial Lift
R&D Council

Worst-case conditions for well that can support fluid level to surface






> Supply pressure can vary significantly during course of year.






A valve that appears to be "open" may really be closed...




Surface opening and closing pressures should drop sequentially






Transfer Point Pressures should be greater than Production Pressures





Minimum Mandrel Spacing

▶ The minimum spacing between mandrels is 450-650 feet TVD.




Based on P _{KO} = 1200 psi, P _{io} = 1050 -1000 psi			
BFPD	Minimum Spacing (TVD)		
*50- 100	800' - 750'		
100-200	750' – 650'		
200-500	650' – 500'		
500-5000	500' – 450'		

^{*}When no un-tapped potential is available behind pipe



Use Bracketing when Appropriate






Placement of Top Mandrel



The top valve should be placed at or above the depth of the static fluid level that can be supported by the reservoir pressure.

Do I really need to space the top valve from the top?



Placement of Bottom Mandrel



- For installations with side-pocket mandrels, the bottom mandrel should be placed 1-2 joints above the packer.
- For installations with conventional mandrels, the bottom mandrel should be placed at the maximum anticipated depth of injection that can be achieved during the target producing period.

Are Test Rack Opening Pressures Correct?



Spot check the valve calculations to ensure they are performed correctly, paying particular attention to the selection of Ap/Ab.

(These will be different for valves with TC trim than for valves with Monel trim)

Port Size (1/64")	Bellows Area (sq. inch)	Monel A _p /A _b	Tungsten Carbide A _p /A _b	
1" Equipment				
8	0.31	0.042	0.068	
10	0.31	0.067	0.088	
12	0.31	0.094	0.119	
16	0.31	0.165	0.187	
20	0.31	0.255	0.313	
24	0.31	0.365	0.416	
1-1/2" Equipment				
8	0.77	0.017	0.027	
12	0.77	0.038	0.048	
16	0.77	0.066	0.075	
20	0.77	0.103	0.126	
24	0.77	0.147	0.168	
28	0.77	0.200	0.216	
32	0.77	0.260	0.299	

Each valve should pass at least 100-200 MSCFD during unloading




- ► Use VPC analysis to evaluate gas passage.
- ightharpoonup Evaluate valve performance at $P_{inj} = P_{iod}$ plus dP between stations.
- ► Kick-off simulator in SNAP can give a more realistic estimate of gas requirements.

Design should work over a range of conditions



Perform a sensitivity analysis and evaluate the performance of the gas lift system to ensure that it will meet the above criteria at various points in time over the anticipated operating life.



Discussion

How do these guidelines compare to the designs in your wells?

Which of these practices do you see the most benefit in using?

Are there any guidelines you disagree with? What would you do differently?



Break

Artificial Lift
R&D Council

- Stretch and move!
- Please return in 15 minutes.



Exercise: Evaluate your design using dynamic simulation



Evaluate your new gas lift design using the transient gas lift simulator in Prosper.



Discussion

Did your design perform as expected? If not, why not?

What would you do differently next time?



Design Reviews

► Shows us your wells!



Break

Artificial Lift
R&D Council


- Stretch and move!
- Please return in 15 minutes.



Trouble-shooting Gas Lift Wells with SNAP

Artificial Lift R&D Council

Intro to Gas Lift Surveillance Dashboard



Trouble-shooting Exercise




Use the SNAP Surveillance Dashboard to trouble-shoot one of your wells. Be prepared to present your results after lunch.

Well Reviews



Show us your wells!



Discussion

What were your major findings?

What follow-up actions will you take?



Copyright



Rights to this presentation are owned by the company(ies) and/or author(s) listed on the title page. By submitting this presentation to the Gas-Lift Workshop, they grant to the Workshop, the Artificial Lift Research and Development Council (ALRDC) rights to:

- Display the presentation at the Workshop.
- Place it on the <u>www.alrdc.com</u> web site, with access to the site to be as directed by the Workshop Steering Committee.
- Links to presentations on ALRDC's social media accounts.
- ▶ Place it on an USB/CD for distribution and/or sale as directed by the Workshop Steering Committee.

Other uses of this presentation are prohibited without the expressed written permission of the company(ies) and/or author(s) who own it and the Workshop Steering Committee.

Disclaimer



The following disclaimer shall be included as the last page of a Technical Presentation or Continuing Education Course. A similar disclaimer is included on the front page of the Gas-Lift Workshop Web Site.

The Artificial Lift Research and Development Council and its officers and trustees, and the Gas-Lift Workshop Steering Committee members, and their supporting organizations and companies (here-in-after referred to as the Sponsoring Organizations), and the author(s) of this Technical Presentation or Continuing Education Training Course and their company(ies), provide this presentation and/or training material at the Gas-Lift Workshop "as is" without any warranty of any kind, express or implied, as to the accuracy of the information or the products or services referred to by any presenter (in so far as such warranties may be excluded under any relevant law) and these members and their companies will not be liable for unlawful actions and any losses or damage that may result from use of any presentation as a consequence of any inaccuracies in, or any omission from, the information which therein may be contained.

The views, opinions, and conclusions expressed in these presentations and/or training materials are those of the author and not necessarily those of the Sponsoring Organizations. The author is solely responsible for the content of the materials.

The Sponsoring Organizations cannot and do not warrant the accuracy of these documents beyond the source documents, although we do make every attempt to work from authoritative sources. The Sponsoring Organizations provide these presentations and/or training materials as a service. The Sponsoring Organizations make no representations or warranties, express or implied, with respect to the presentations and/or training materials, or any part thereof, including any warrantees of title, non-infringement of copyright or patent rights of others, merchantability, or fitness or suitability for any purpose.

11/20/2024

29