

High-Pressure Gas Lift in Unconventional Assets

A Journey from Pioneer to Practice

Tony T. Liao, Salvador Vela, ExxonMobil





Agenda

- ExxonMobil HPGL Highlights
- Criteria for Application
- Pilot Downhole Designs Two Configurations
- Downhole Design Test with SPMs
- Surface Facility Design
- First HPGL Well (Shallower Formation) Performance Analysis
- Integrated Surveillance and Monitoring
- In-depth Well Performance Analyses
- Well Model to Support HPGL Conversion: HPGL, CGL, or ESP?
- Lessons Learned
- Path Forward





ExxonMobil HPGL Highlights

- First pilot HPGL was executed May 2021 with successful performance
- Current HPGL program with ~ 100 wells
- Pilot and early applications featured simple downhole configurations
- Side Packet Mandrels (SPMs) added in the newer designs
- While programs have consistently delivered desired business values, yet they did encounter operational challenges
- HPGL has become an integral part of Permian field development strategy






Criteria for Application


- Above grade
- Schedule 3+ months out for F&C electrical installation (electric compressor only)
- Need at least 1100 MCFD for annular injection
- Dehy installed on centralized compression system preferred
- Wolfcamp A or deeper
- Prefer to limit ("Normal" injection + production gas) to 3 MMCFD going through pad tester due to erosional rates (can go over without major concern)
- Battery constraints do not factor in unless Wolfcamp A well was scoped as CGL and changed to HPGL





Pilot Downhole Designs – Two Configurations












Downhole Design – Test with SPMs



- Annular design
- Configured to run HPGL first, then go CGL directly once HPGL booster moves to other well in ~ 9 months to 1 year
- Save a W/O job with Side Pocket Mandrels (SPMs)
- Many model runs were made to confirm the advantages of tapered tubing string for both HPGL first and when operation is switched to CGL later
- Hybrid tubing w/ 2 7/8" for top 5,000' and 2
 3/8" for rest of string
- Side pocket mandrels for all valves
- Use cross-overs in 2 7/8" section for SPMs
- Only live valve is orifice
- EOT has packer
- Sliding sleeves above packer



Surface Facility Design



- Injection
 - Normal injection line is blinded, and temporary surface injection line is built from injection meter skid to booster compressor
 - Booster sends high pressure gas through 1502 injection line to wellhead
- Liquids
 - Temporary surface scrubber line installed between compressor skid and flowline header
- 1&E
 - Permissives are added on the flowline header, compressor discharge line, and wellhead casing to shutdown compressor and ESD well



Compressor

COMPRESSION

(booster)


Booster)/ 150 Hp EL)

- CAT G3306B NA Engine/ TECO 150 Electric
- Ariel JGQ/2
- 145 BHP X 1800 RPM
- 1ST STAGE CYLINDER 2-3/4" RJ 2500 psig
- 2ND STAGE CYLINDER 1-5/8" RJ 5500 psig




Booster Compressor Performance

Single Stage - Two Stage







Injection Meter Skid P&ID





Compressor Liquid Dump Line to Commingled Flowline






Surface Facility



Injection Meter Skid Connection to ANSI 600 Flanged Injection Line

Injection Line Connection to Compressor

Injection Line to Wellhead




Surface Facility (Cont'd)



High Pressure Connection to WH



Liquid Scrubber Line to Flowline Header



Liquid Dump Line to Flowline





First HPGL Well (Shallower Formation) Analysis



Formation: XYZ

POP on AFL: 5/29/2021

■ HPGL Injection Start: 5/29/2021

 Downtime: Multiple days of DT due to electrical PME issues between June and

September

Injection Rates:

- Initial: 1100 MCFD

- 7/15-10/18: 1400 MCFD

- 10/19-11/29: 1300 MCFD

HPGL End: 12/1/2021CGL Start: 12/14/2021

CGL injection rate: 550 MCFD


CGL continued well decline trend where

HPGL ended





First Pilot HPGL Well Compared to Closest ESPS





First Pilot Well HPGL Performance Compared to CGL

- Well models were created and calibrated to selected representative dates for HPGL operating conditions
- Calibrated models were used to simulate typical AGL & CGL performance & compared with HPGL for the same dates and conditions
- HPGL would outperform AGL by ~ 22% on average for all the dates examined, or an average gain of ~ 90
 BOPD for HPGL over AGL
- HPGL would outperform CGL by \sim 55% on average for all the dates examined, or an average gain of \sim 180 BOPD for HPGL over CGL
- The net profit from HPGL is significantly more than CGL for 180 days

First Pilot Well HPGL Comparison to AGL & CGL							
Date	HGPL, BOPD	AGL, BOPD	Diff over AGL BOPD	% over AGL	CGL, BOPD	Diff over CGL BOPD	% over CGL
5/31/2021	471	379	92	24%	267	204	76%
6/14/2021	559	427	132	31%	331	228	69%
7/9/2021	583	472	111	24%	375	208	55%
8/9/2021	494	418	76	18%	341	153	45%
10/3/2021	398	356	42	12%	304	94	31%
Average	501	410	91	22%	324	177	55%

HPGL Ended HPGL Days BO over CGL 11/26/2021 179 xyz

Assumptions:

AGL: Pinj=1050 psi, deltaP valve=100 psi, QGI=1200 MCFD, optimum injection depth. Most optimistic case.

CGL: Pinj=1050 psi, deltaP valve=100 psi, QGI=600 MCFD, optimum injection depth. Most optimistic case.






HPGL Integrated Well Surveillance and Monitoring








In-depth HPGL Well Performance Analyses





Well Model to Support HPGL Conversion: HPGL, CGL, or ESP?







Lesson Learned

- Liquid Dump Line/Scrubber System
 - ✓ Issue: Compressor would consistently go down on low suction pressure due to scrubber dump hanging open
 - ✓ Solution: Insulated and heat traced dump valve/back pressure valve and dump line on skid to prevent freezing during winter
- ESD Function
 - ✓ Issue: Injection pressure is too high and 1502 will not allow for steel line to pull gas for ESD
 - ✓ Solution: Run steel line from wellhead next to HPGL to run ESD or just run off of nitrogen
- Injection Rates
 - ✓ Issue: No data for optimal injection set point
 - ✓ Solution: 900mcf and 1100mcf used for testing but bumping injection up to 1300mcf+ has shown increased drawdown and higher production
- Compressor Controls
 - ✓ Issue: Three ways to run compressor 1) Set cyclonic for a set volume and match Hz on compressor for volume 2) Set cyclonic to hold set suction pressure and set Hz on compressor to run at set volume 3) Set suction control valve on inlet of compressor
 - ✓ Solution: Option 2 allows compressor to run smoother and less headache with low suction. This option also utilizes
 what we already have by using the cyclonic for the suction control





HPGL Path Forward

- Well Selection
 - ✓ Work with reservoir group to select wells for application
 - ✓ List sent out for OPS engineering group to evaluate compression
- F&C Scope of Work
 - ✓ Meet with F&C on location to walk through build
 - ✓ Add to F&C scope of work pre-PSSR
- Field Operations
 - ✓ Meet with representative on location from each field office to walk through operations
- Capital Efficiency
 - ✓ Establish program for moving of equipment to reuse and working with supply chain group on transferring charges (just like ESP surface equipment)
- Execution Strategy
 - ✓ Program manages changes to development strategy and evaluation from ops/reservoir on forecasting for compression





Question Time





Copyright

- Rights to this presentation are owned by the company(ies) and/or author(s) listed on the title
 page. By submitting this presentation to the Gas Lift Workshop, they grant to the Workshop,
 and the Artificial Lift Research and Development Council (ALRDC) rights to:
 - Display the presentation at the Workshop.
 - Place the presentation on the <u>www.alrdc.com</u> web site, with access to the site to be as directed by the Workshop Steering Committee.
 - Place the presentation for distribution and/or sale as directed by the Workshop Steering Committee.
- Other uses of this presentation are prohibited without the expressed written permission of the company(ies) and/or author(s).



Disclaimer

- The following disclaimer shall be included as the last page of a Technical Presentation or Continuing Education Course. A similar disclaimer is included on the Gas Lift Workshop webpage.
- The Artificial Lift Research and Development Council and its officers and trustees, and the Gas Lift Workshop Steering Committee members, and their supporting organizations and companies (here-in-after referred to as the Sponsoring Organizations), and the author(s) of this Technical Presentation or Continuing Education Course and their company(ies), provide this presentation and/or training material at the Gas Lift Workshop "as is" without any warranty of any kind, express or implied, as to the accuracy of the information or the products or services referred to by any presenter (in so far as such warranties may be excluded under any relevant law) and these members and their companies will not be liable for unlawful actions and any losses or damage that may result from use of any presentation as a consequence of any inaccuracies in, or any omission from, the information which therein may be contained.
- The views, opinions, and conclusions expressed in these presentations and/or training materials are those of the author and not necessarily those of the Sponsoring Organizations. The author is solely responsible for the content of the materials.
- The Sponsoring Organizations cannot and do not warrant the accuracy of these documents beyond the source documents, although we do make every attempt to work from authoritative sources. The Sponsoring Organizations provide these presentations and/or training Organizations make no representations or warranties, express or implied, with respect to the presentations and/or training materials, or any part thereof, including any warrantees of title, non-infringement of copyright or patent rights of others, merchantability, or fitness or suitability for any purpose.



Disclaimer

- The following disclaimer shall be included as the last page of a Technical Presentation or Continuing Education Course. A similar disclaimer is included on the Gas Lift Workshop webpage.
- The Artificial Lift Research and Development Council and its officers and trustees, and the Gas Lift Workshop Steering Committee members, and their supporting organizations and companies (here-in-after referred to as the Sponsoring Organizations), and the author(s) of this Technical Presentation or Continuing Education Course and their company(ies), provide this presentation and/or training material at the Gas Lift Workshop "as is" without any warranty of any kind, express or implied, as to the accuracy of the information or the products or services referred to by any presenter (in so far as such warranties may be excluded under any relevant law) and these members and their companies will not be liable for unlawful actions and any losses or damage that may result from use of any presentation as a consequence of any inaccuracies in, or any omission from, the information which therein may be contained.
- The views, opinions, and conclusions expressed in these presentations and/or training materials are those of the author and not necessarily those of the Sponsoring Organizations. The author is solely responsible for the content of the materials.
- The Sponsoring Organizations cannot and do not warrant the accuracy of these documents beyond the source documents, although we do make every attempt to work from authoritative sources. The Sponsoring Organizations provide these presentations and/or training Organizations make no representations or warranties, express or implied, with respect to the presentations and/or training materials, or any part thereof, including any warrantees of title, non-infringement of copyright or patent rights of others, merchantability, or fitness or suitability for any purpose.